

Features

- 316 stainless steel body, ball, & stem
- RTFE (reinforced Teflon) ball seats
- Triple PTFE/Viton live loaded stem seals, adjustable
- Valves are tested per API 598
- Spring Return or Double Acting Actuators
- Type IP66 & IP68 weatherproof actuator
- Rugged scotch yoke construction tested for 1 million+ cycles
- Anodized aluminum body with epoxy-polyester end covers
- Namur and ISO mounting standards
- Highly visible valve position indicator
- Actuator factory lubricated for normal lifetime

Applications

On-off control of water, air, oil, and other media compatible with the materials of construction. Cycle times 1 to 3 seconds per 90° rotation. Suitable for vacuum service to 29.92 InHg (2.3 x 10⁻³ Torr).

Operation

Double acting scotch yoke actuators use air pressure to open and air pressure to close the ball valve (4-way pilot). Spring return scotch yoke actuators use air pressure to open and springs to close the ball valve (3-way pilot). Actuator will work with filtered dry or lubricated compressed air. Recommended air supply pilot pressure should be between 58 and 87 PSI. Easy to read visual valve position indicator located on top of actuator.

Construction

Valve Body	316 Stainless Steel ASTM A351 CF8M
Ball/Stem	316 Stainless Steel
Ball Seats	RTFE (reinforced Teflon)
Stem Seals	PTFE/ Viton
Anti-Static Device	Ball to Stem (1/4" - 4") + Stem to Body (1-1/2" - 4")
Actuator Seals	NBR
Actuator Body/ End Covers	Hard anodized aluminium/ Polyester coated aluminium
Position Indicator	Glass filled Polyamide
Fasteners	ASTM 304 Stainless Steel



Description

Heavy duty quarter turn scotch yoke actuators designed for long life and tested for a minimum 1 million+ operations. Investment cast 2 piece full port stainless steel body/ball for unrestricted flow and minimum pressure loss. Adjustable live loaded stem seal packing helps compensate for wear, pressure or temperature fluctuations, extending the cycle life of the valve. Blow-out proof stem. Standard Namur mounting pads for optional accessory confirmation switches and pilot valves.


Approvals– Actuators

- CE conformance– MD 2006/42/CE
- EN ISO 12100:2010
- EN ISO 4414:2010
- ISO5211/ DIN3337 valve mounting
- Namur VDI/VDE 3845 accessory mounting
- SIL3– EN 17955:2024 & IEC 61508-1/-2:2010

Standards– Valves

- Design: API 608
- Testing: API 598
- Threaded Connection: ASME B1.20.1 (NPT)/ ISO 228-1/ BS21
- Pressure/Temperature Rating: ASME B16.34
- Marking: MSS SP-25
- CE conformance- EPED 2014/68/UE

Features



Pressure Rating

Pressure Rating*: 1000 PSI (69 Bar) (1/4"-2")
800 PSI (55 Bar) (2-1/2"-4") CWP non-shock,
Vacuum 29.92 InHg (2.3 x 10⁻³ Torr)

*See P/T Chart

Pilot Air Pressure: 43-120 PSI (3-8 Bar)

Pilot Air Pressure- Recommended: 58-87 PSI (4-6 Bar)

Pilot Air Pressure- Maximum: 120 PSI (8 Bar)

Temperature Rating

Valve Temperature Rating: -4° to 392° F (-20 to 200°C)

Actuator Temperature Rating: -4 to 167° F (-20 to 75° C)

*See P/T chart



Optional Accessories

- DMS: Direct Mount Solenoid
- pilot to electrically operate the ball valve
- VPS: Valve Position Switches
- limit switches to confirm valve position
- HTB: High Temperature Bracket
- increases media working temperature
- DSP: Digital Smart Positioner
- simplify throttling applications

Specifications (English units)

Stock Number	Pipe Size (NPT)	Orifice Size (inch)	Cv Flow Factor	Pressure Max.(PSI)*	Cycle Time /90° (open-close)	Pilot Air Port (NPT)	Air Volume (standard cubic inches)
VALVE WITH SPRING RETURN ACTUATOR							
553602A	1/4	0.5	6.9	1000	1-1	1/4	73.2
553603A	3/8	0.5	6.9	1000	1-1	1/4	73.2
553604A	1/2	0.6	9.7	1000	1-1	1/4	73.2
553606A	3/4	0.8	18.4	1000	1-1	1/4	73.2
553608A	1	1.0	55.4	1000	1-1	1/4	109.8
553610A	1-1/4	1.3	89.7	1000	1-1	1/4	109.8
553612A	1-1/2	1.5	144.2	1000	1-1	1/4	109.8
553616A	2	2.0	226.0	1000	1-1	1/4	256.3
553620A	2-1/2	2.6	289.0	800	1-1	1/4	512.6
553624A	3	3.1	454.0	800	3-1	1/4	1067.9
553632A	4	3.9	710.0	800	3-1	1/4	1665.9
VALVE WITH DOUBLE ACTING ACTUATOR							
553502A	1/4	0.5	6.9	1000	1-1	1/4	146.5
553503A	3/8	0.5	6.9	1000	1-1	1/4	146.5
553504A	1/2	0.6	9.7	1000	1-1	1/4	146.5
553506A	3/4	0.8	18.4	1000	1-1	1/4	146.5
553508A	1	1.0	55.4	1000	1-1	1/4	146.5
553510A	1-1/4	1.3	89.7	1000	1-1	1/4	146.5
553512A	1-1/2	1.5	144.2	1000	1-1	1/4	219.7
553516A	2	2.0	226.0	1000	1-1	1/4	219.7
553520A	2-1/2	2.6	289.0	800	1-1	1/4	402.8
553524A	3	3.1	454.0	800	1-1	1/4	402.8
553532A	4	3.9	710.0	800	1-1	1/4	842.1

Cv= The GPM of water at 60° F that will pass through the valve with 1 PSI pressure drop

* Pressure @ 0 to100° F (reduced pressure at higher temperatures – see P/T chart)

Specifications (Metric units)


Stock Number	Pipe Size (NPT)	Orifice Size (mm)	Kv Flow Factor	Pressure Max.(Bar)*	Cycle Time/90° (open-close)	Pilot Air Port (NPT)	Air Volume (standard liters)
VALVE WITH SPRING RETURN ACTUATOR							
553602A	1/4	11.5	5.9	69	1-1	1/4	1.2
553603A	3/8	12.5	5.9	69	1-1	1/4	1.2
553604A	1/2	15.0	8.4	69	1-1	1/4	1.2
553606A	3/4	20.0	15.9	69	1-1	1/4	1.2
553608A	1	25.0	47.9	69	1-1	1/4	1.8
553610A	1-1/4	32.0	77.6	69	1-1	1/4	1.8
553612A	1-1/2	38.0	124.7	69	1-1	1/4	1.8
553616A	2	50.0	195.5	69	1-1	1/4	4.2
553620A	2-1/2	65.0	250.0	55	1-1	1/4	8.4
553624A	3	80.0	392.7	55	3-1	1/4	17.5
553632A	4	100.0	614.2	55	3-1	1/4	17.5
VALVE WITH DOUBLE ACTING ACTUATOR							
553502A	1/4	11.5	5.9	69	1-1	1/4	2.4
553503A	3/8	12.5	5.9	69	1-1	1/4	2.4
553504A	1/2	15.0	8.4	69	1-1	1/4	2.4
553506A	3/4	20.0	15.9	69	1-1	1/4	2.4
553508A	1	25.0	47.9	69	1-1	1/4	2.4
553510A	1-1/4	32.0	77.6	69	1-1	1/4	2.4
553512A	1-1/2	38.0	124.7	69	1-1	1/4	3.6
553516A	2	50.0	195.5	69	1-1	1/4	3.6
553520A	2-1/2	65.0	250.0	55	1-1	1/4	6.6
553524A	3	80.0	392.7	55	1-1	1/4	6.6
553532A	4	100.0	614.2	55	1-1	1/4	13.8

* Pressure range @ -18 to 38°C (reduced pressure for higher temperatures—see P/T chart)

Pressure/Temperature Chart


Pressure/Temp. Chart - 1000 PSI (69 Bar)

P/T Chart (PSI/°F)				
PSI	1000	1000	100	0
°F	-4	50	330	392




Pressure/Temp. Chart - 800 PSI (55 Bar)

P/T Chart (PSI/°F)				
PSI	800	800	100	0
°F	-4	50	330	392




Pressure/Temp. Chart - 69 Bar (1000 PSI)

P/T Chart (BAR/°C)				
Bar	69	69	7	0
°C	-20	10	166	200




Pressure/Temp. Chart - 55 Bar (800 PSI)

P/T Chart (BAR/°C)				
Bar	55	55	7	0
°C	-20	10	166	200




Dimensions: Spring Return



Pipe Size		A	B* (SR)	C	D	E	F	G	J	K	P	A & B Ports (NPT)	Weight
1/4	inch	2.6	10.1	4.9	2.9	4.2	5.5	5.1	1.5	1.2	0.5	1/4	4.5 lb
	mm	65.3	256.5	124.5	73.7	106.7	139.7	129.5	37.0	31.0	11.5		2.0 kg
3/8	inch	2.6	10.1	4.9	2.9	4.2	5.5	5.1	1.5	1.2	0.5	1/4	4.5 lb
	mm	65.3	256.5	124.5	73.7	106.7	139.7	129.5	37.0	31.0	12.5		2.0 kg
1/2	inch	2.6	10.1	4.9	2.9	4.2	5.5	5.1	1.5	1.2	0.6	1/4	4.3 lb
	mm	65.3	256.5	124.5	73.7	106.7	139.7	129.5	37.0	31.0	15.0		1.9 kg
3/4	inch	3.0	10.1	5.2	2.9	4.5	6.0	5.1	1.8	1.5	0.8	1/4	4.7 lb
	mm	77.3	256.5	132.1	73.7	114.3	152.4	129.5	45.0	38.9	20.0		2.1 kg
1	inch	3.5	12.3	6.2	3.5	5.5	7.2	6.2	2.1	1.7	1.0	1/4	8.3 lb
	mm	88.7	314.0	157.5	88.9	139.7	182.9	157.5	53.5	44.3	25.0		3.8 kg
1-1/4	inch	4.0	12.3	6.4	3.5	5.7	7.7	6.2	2.3	2.0	1.3	1/4	9.2 lb
	mm	102.4	314.0	162.6	88.9	144.8	195.6	157.5	59.0	50.7	32.0		4.2 kg
1-1/2	inch	4.3	12.3	7.0	3.5	6.3	8.5	6.2	2.9	2.2	1.5	1/4	10.9 lb
	mm	109.0	314.0	177.8	88.9	160.0	215.9	157.5	74.8	55.0	38.0		4.9 kg
2	inch	4.9	16.5	8.1	3.9	7.4	9.9	8.3	3.3	2.4	2.0	1/4	18.0 lb
	mm	125.3	419.1	205.7	99.1	188.0	251.5	210.8	83.5	62.2	50.0		8.2 kg
2-1/2	inch	6.5	19.6	10.0	5.0	9.3	12.0	9.8	4.3	3.2	2.6	1/4	35.0 lb
	mm	165.0	497.8	254.0	127.0	236.2	304.8	248.9	108.8	82.5	65.0		15.9 kg
3	inch	7.5	23.8	11.4	5.9	10.7	14.0	11.9	4.7	3.7	3.1	1/4	58.4 lb
	mm	189.5	604.5	289.6	149.9	271.8	355.6	302.3	118.3	94.8	80.0		26.5 kg
4	inch	9.4	23.8	12.8	5.9	12.1	16.0	11.9	6.1	4.7	3.9	1/4	73.6 lb
	mm	238.0	604.5	325.1	149.9	307.3	406.4	302.3	153.8	119.0	100.0		33.4 kg

Dimensions: Double Acting



Pipe Size		A	B	C	D	E	F	G	J	K	P	A & B Ports (NPT)	Weight
1/4	inch	2.6	10.1	4.9	2.9	4.2	5.5	5.1	1.5	1.2	0.5	1/4	4.5 lb
	mm	65.3	256.5	124.5	73.7	106.7	139.7	129.5	37.0	31.0	11.5		2.0 kg
3/8	inch	2.6	10.1	4.9	2.9	4.2	5.5	5.1	1.5	1.2	0.5	1/4	4.5 lb
	mm	65.3	256.5	124.5	73.7	106.7	139.7	129.5	37.0	31.0	12.5		2.0 kg
1/2	inch	2.6	10.1	4.9	2.9	4.2	5.5	5.1	1.5	1.2	0.6	1/4	4.3 lb
	mm	65.3	256.5	124.5	73.7	106.7	139.7	129.5	37.0	31.0	15.0		1.9 kg
3/4	inch	3.0	10.1	5.2	2.9	4.5	6.0	5.1	1.8	1.5	0.8	1/4	4.7 lb
	mm	77.3	256.5	132.1	73.7	114.3	152.4	129.5	45.0	38.9	20.0		2.1 kg
1	inch	3.5	12.3	6.2	3.5	5.5	7.2	6.2	2.1	1.7	1.0	1/4	8.3 lb
	mm	88.7	314.0	157.5	88.9	139.7	182.9	157.5	53.5	44.3	25.0		3.8 kg
1-1/4	inch	4.0	12.3	6.4	3.5	5.7	7.7	6.2	2.3	2.0	1.3	1/4	9.2 lb
	mm	102.4	314.0	162.6	88.9	144.8	195.6	157.5	59.0	50.7	32.0		4.2 kg
1-1/2	inch	4.3	12.3	7.0	3.5	6.3	8.5	6.2	2.9	2.2	1.5	1/4	10.9 lb
	mm	109.0	314.0	177.8	88.9	160.0	215.9	157.5	74.8	55.0	38.0		4.9 kg
2	inch	4.9	16.5	8.1	3.9	7.4	9.9	8.3	3.3	2.4	2.0	1/4	18.0 lb
	mm	125.3	419.1	205.7	99.1	188.0	251.5	210.8	83.5	62.2	50.0		8.2 kg
2-1/2	inch	6.5	9.9	9.1	3.9	8.4	11.1	5.0	4.3	3.2	2.6	1/4	22.9 lb
	mm	165.0	251.5	231.1	99.1	213.4	281.9	127.0	108.8	82.5	65.0		10.4 kg
3	inch	7.5	9.9	9.5	3.9	8.8	12.1	5.0	4.7	3.7	3.1	1/4	28.9 lb
	mm	189.5	251.5	241.3	99.1	223.5	307.3	127.0	118.3	94.8	80.0		13.1 kg
4	inch	9.4	12.2	11.8	5.0	11.1	15.0	6.1	6.1	4.7	3.9	1/4	50.7 lb
	mm	238.0	309.9	299.7	127.0	281.9	381.0	154.9	153.8	119.0	100.0		23.0 kg